


**TUBE:**

- ▶ White Plasticized PVC

**REINFORCEMENT:**

- ▶ High Tensile Synthetic Textile

**COVER:**

- ▶ Abrasion, Ozone & Weather Resistant Blue PVC

**TEMP RANGE:**

- ▶ -10°C Approx to +65°C Approx

**APPLICATIONS:**

- ▶ Widely Used for Irrigation & Washing in the Parks, Community, Factories & Households.

**PROPERTIES:**

- ▶ Torsion Free - Non Kinking Hose
- ▶ Germproof Inner PVC Layer. It Will not Produce Fungus or Moss even if it is not used for a long time.
- ▶ Good Resistance to UV & Ozone
- ▶ 24 Strips of Fibre in the Middle Layer Can Resist High Water Pressure.
- ▶ No fissure or crack openings will develop on exposure to Sun.

**FEATURES:**

- ▶ Light Weight, Soft & Elastic
- ▶ Durable, Smooth Surface

**STANDARD COLOUR:**

- ▶ Blue With Yellow Strip

**MARKING ON THE HOSE:**

- ▶ TUBITEC TORSION FREE GARDEN HOSE SIZE...mm..WP..BAR



ITEM Code	ID mm	OD mm	WALL THICKNESS mm	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS mm	WEIGHT Kg/Coil	STANDARD LENGTH mtr	VACCUM PRESSURE Bar	EX-STOCK ---	MOQ Coils
				Bar	PSI	Bar	PSI						
15GRD1230	12.00	17.00	2.50	7	100	21	305	-	4.50	30	-	YES	1
15GRD1250	12.00	17.00	2.50	7	100	21	305	-	7.50	50	-	YES	1
15GRD12100	12.00	17.00	2.50	7	100	21	305	-	15.00	100	-	YES	1
15GRD2030	20.00	26.00	3.00	7	100	21	305	-	8.70	30	-	YES	1
15GRD2050	20.00	26.00	3.00	7	100	21	305	-	14.50	50	-	YES	1
15GRD20100	20.00	26.00	3.00	7	100	21	305	-	29.00	100	-	YES	1
15GRD2530	25.00	31.00	3.00	6	85	18	260	-	10.50	30	-	YES	1
15GRD2550	25.00	31.00	3.00	6	85	18	260	-	17.50	50	-	YES	1
15GRD25100	25.00	31.00	3.00	6	85	18	260	-	35.00	100	-	YES	1

Specification Subject to change due to Improvement in Quality ( E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.