


TUBE:

- ▶ High Grade Soft PVC

REINFORCEMENT:

- ▶ Spring Steel Wire

COVER:

- ▶ High Grade Soft PVC

TEMP RANGE:

- ▶ -10 °C Approx. to +70 °C Approx.
- ▶ Short Time to +80 °C Approx

APPLICATIONS:

- ▶ For Powdery Solids Such As Dust, Powder & Fibres
- ▶ For Gaseous Media Such As Vapors & Smoke
- ▶ For Air Conditioning & Ventilation Technology

PROPERTIES:

- ▶ Good Resistance To Alkalis, Acids Chemical Resistant.
- ▶ Flame Retardant Acc To UL94-HB
- ▶ Super-Light, Kink-Proof and Excellent Compressibility 3:1
- ▶ Capable Of Electrostatic Discharge By Grounding The Spiral.

STANDARD COLOUR:

- ▶ Grey and Transparent

MARKING ON THE HOSE:

NA



ITEM	ID	OD	WALL THICKNES S	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11PVCFLEX38	38.00	46.00	-	0.50 -	- -	46	0.26	15	0.18	YES	15
11PVCFLEX50	50.00	58.00	-	0.40 -	- -	58	0.30	15	0.15	YES	15
11PVCFLEX63	63.00	72.00	-	0.30 -	- -	72	0.33	15	0.10	YES	15
11PVCFLEX76	76.00	85.00	-	0.27 -	- -	85	0.40	15	0.08	YES	15
11PVCFLEX100	100.00	109.00	-	0.20 -	- -	109	0.57	15	0.05	YES	15
11PVCFLEX125	125.00	134.00	-	0.16 -	- -	134	0.77	15	0.03	YES	15
11PVCFLEX150	150.00	159.00	-	0.14 -	- -	159	0.90	15	0.03	YES	15
11PVCFLEX203	203.00	213.00	-	0.10 -	- -	213	1.30	10	0.03	YES	10

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.