


TUBE:

- ▶ EVA

REINFORCEMENT:

- ▶ Self Supporting Profile Construction

COVER:

- ▶ Open Profile Geometry

TEMP RANGE:

- ▶ -45 °C Approx. to +65 °C Approx

APPLICATIONS:

- ▶ For Domestic & Industrial Vacuum Cleaners
- ▶ For Cleaning Of Swimming Pools

PROPERTIES:

- ▶ Good Resistance To Alkalis, Acids, UV & Ozone
- ▶ Light Model, Highly Flexible, Crush-Proof, Floatable
- ▶ Gas & Liquid Tight

STANDARD COLOUR:

- ▶ Black

MARKING ON THE HOSE:

- ▶ NA



ITEM	ID	OD	WALL THICKNES S	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUM PRESSURE	EX-STOCK	MOQ		
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11EVA25	25.00	32.20	-	-	-	-	-	66	0.15	20	0.50	YES	5
11EVA32	32.00	40.40	-	-	-	-	-	82	0.24	20	0.50	YES	5
11EVA38	38.00	47.20	-	-	-	-	-	93	0.31	20	0.50	YES	5
11EVA50	50.00	60.40	-	-	-	-	-	121	0.44	20	0.50	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.