


**TUBE:**

- ▶ Black colour, Synthetic rubber resistant to oil and water.

**REINFORCEMENT:**

- ▶ Four high tensile steel wire spirals.

**COVER:**

- ▶ Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone.

**TEMP RANGE:**

- ▶ Continuous: -40°C to +90°C

**APPLICATIONS:**

- ▶ Water blasting, Water jetting, cleaning equipment. Delivery of water and water emulsions.
- ▶ Cleaning and Preparation of Marine Surfaces Runway and Swimming Pool

**FEATURES:**

- ▶ Highly Abrasion resistant Cover
- ▶ Exceeds ISO 7751 Performance Requirements

**STANDARD COLOUR:**

- ▶ Black

**Applicable Standard :**

- ▶ EN1829-2



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDAR	VACCUM	EX-STOCK	MOQ
				Bar	PSI	Bar	PSI			D LENGTH	PRESSURE		
501JB1106	9.50	20.60	15.05	1100	15950	2750	39875	155	0.82	60	-	NO	60
501JB1108	12.70	27.00	19.85	1100	15950	2750	39875	200	1.53	60	-	YES	1
501JB1112	19.00	32.00	25.50	1100	15950	2750	39875	310	2.07	60	-	NO	60

Specification Subject to change due to Improvement in Quality ( E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.