


TUBE:

- ▶ UHMWPE, White, Smooth, Food Quality & Abrasion Resistant.
- ▶ Complies FDA Standards.

REINFORCEMENT:

- ▶ Synthetic Plies, Helix Wire Embedded, Antistatic Copper Wire.

TEMPERATURE RANGE:

- ▶ -25°C Cleaning Upto 130°C For Max 30 Min In Open System.
- ▶ Temp & Concentration Of The Transported Medium :Refer To Chemical Resistance Chart.

COVER:

- ▶ Special Blue Rubber, Abrasion, Ozone & Weather Resistant.
- ▶ Smooth With Fabric Impression.

APPLICATIONS:

- ▶ Multipurpose Suction & Delivery Hose designed for Acids, Bases, Ketons, Aldehyds, Esters, Aromatic & Aliphatic Hydrocarbons.
- ▶ Suitable for Animal or Vegetable Foodstuffs & Alcoholic Drinks.

FEATURES:

- ▶ Complying with FDA standards
- ▶ Free from Phthalates, Animal Derivatives, Adipates, Plasticizers & Bisphenol A.

STANDARD COLOUR:

- ▶ Outer Cover - Blue
- ▶ Inner layer - White

MARKING ON THE HOSE:


ITEM Code	ID mm	OD mm	WALL THICKNESS mm	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS mm	WEIGHT Kg/mtr	STANDAR D	VACCUM	EX-STOCK	MOQ
				Bar	PSI	Bar	PSI			LENGTH mtr	PRESSURE Bar		
501ALCF20019	19.00	32.00	6.50	16	232	48	696	190	1.08	40	0.90	YES	1
501ALCF20025	25.00	36.00	5.50	16	232	48	696	250	1.17	40	0.90	YES	1
501ALCF20032	32.00	43.00	5.50	16	232	48	696	315	1.38	40	0.90	YES	1
501ALCF20038	38.00	51.00	6.50	16	232	48	696	375	1.58	40	0.90	YES	1
501ALCF20051	51.00	66.00	7.50	16	232	48	696	500	2.24	40	0.90	YES	1
501ALCF20064	64.00	80.00	8.00	16	232	48	696	625	2.79	40	0.80	YES	1
501ALCF20076	76.00	92.00	8.00	16	232	48	696	750	3.71	40	0.80	YES	1
501ALCF200102	102.00	120.00	9.00	16	232	48	696	1000	5.26	40	0.80	YES	1

Specification Subject to change due to Improvement in Quality (E&O.E).
 In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.