


TUBE:

- Specially Compounded Abrasion Resistant Natural Rubber, High Resilience

REINFORCEMENT:

- High Tensile Synthetic Plies with Copper Wire

COVER:

- Black Abrasion Resistant Natural Rubber Cover
- Wrap Finish

TEMP RANGE:

- -40°C to +70°C Approx

APPLICATIONS:

- For Shot & Sand Blasting Applications that Help in Clearing Metal Surfaces, Etching Glass or Smoothing Casting.

PROPERTIES:

- High Abrasion Resistance
- Seamless
- Uniform Thickness
- Flexible

APPLICABLE STANDARDS:

- IS 5894

STANDARD COLOUR:

- Inner Tube : Black
- Outer Cover : Black

MARKING ON THE HOSE:

- Indo-Maksson Toughline Sandblast Hose 12
- I.D W.P India



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1SBL12KG31.5	31.00	48.00	8.50	12 175	36 525	-	-	40	-	YES	5
1SBL12KG38	38.00	54.00	8.00	12 175	36 525	-	-	40	-	YES	5
1SBL12KG50	50.00	72.00	11.00	12 175	36 525	-	-	40	-	NO	40
1SBL12KG63	63.00	-	-	12 175	36 525	-	-	40	-	YES	5
1SBL12KG75	75.00	-	-	12 175	36 525	-	-	40	-	NO	40
1SBL12KG100	100.00	-	-	12 175	36 525	-	-	40	-	NO	40

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.