


TUBE:

► Specially Compounded Synthetic Rubber, Black

REINFORCEMENT:

► High Strength Synthetic Plies

COVER:

► Black Synthetic Rubber Cover

TEMPERATURE RANGE:

► -40°C Approx to +70°C Approx

APPLICATIONS:

► For All Heavy Duty Air & Water Applications that Require Seamless Conveyance in any Industry

PROPERTIES:

- Seamless
- Uniform Thickness
- Very Strong

STANDARD COLOUR:

- Inner Tube - Black
- Outer Cover - Black

MARKING ON THE HOSE:

- Indo - Maksson Hydro Water Delivery Hose
- I.D W.P India



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1WTR32(P)	31.00	41.00	5.00	10 150	30 450	190	-	40	-	No	40
1WTR38(P)	38.00	48.00	5.00	10 150	30 450	230	-	40	-	No	40
1WTR50(P)	50.00	62.00	6.00	10 150	30 450	310	-	40	-	No	40
1WTR63	63.00	76.00	6.50	10 150	30 450	380	-	20/40	-	YES	5
1WTR75	75.00	87.00	6.00	10 150	30 450	460	-	20/40	-	YES	5
1WTR100	100.00	115.00	7.50	10 150	30 450	610	-	20/40	-	No	20

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.