

FIRE HOSE PU LINED



TUBE:

- TPU Lining

REINFORCEMENT:

- Fabric Reinforced

COVER:

- 100% Virgin Polyester Jacket, Single Jacket

TEMP RANGE:

- -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- Water Discharge, Washdown, Cable & Sling Protection Covers.

FEATURES:

- Light weight & Flexible
- Abrasion Resistant
- Weather & Ozone Resistant

STANDARD COLOUR:

- White



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
FIRE38PUL	38.00	-	-	8	120	24	360	-	-	30	-	YES	30
FIRE50PUL	50.00	-	-	8	120	24	360	-	-	30	-	YES	30
FIRE63PUL	63.00	-	-	8	120	24	360	-	-	30	-	YES	30
FIRE75PUL	75.00	-	-	8	120	24	360	-	-	30	-	YES	30
FIRE100PUL	100.00	-	-	8	120	24	360	-	-	30	-	YES	30
FIRE125PUL	125.00	-	-	8	120	24	360	-	-	30	-	YES	30
FIRE150PUL	150.00	-	-	8	120	24	360	-	-	30	-	YES	30
FIRE200PUL	200.00	-	-	8	120	24	360	-	-	30	-	YES	30

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No. 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558