

FIRE HOSE RUBBER LINED



TUBE:

- Natural Rubber/SBR Tube

REINFORCEMENT:

- Fabric Reinforced

COVER:

- 100% Virgin Polyester Jacket, Single Jacket, Thick Wall.

TEMP RANGE:

- -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- Water Discharge, Washdown, Cable & Sling Protection Covers.

FEATURES:

- Light weight & Flexible
- Abrasion Resistant
- Weather & Ozone Resistant

STANDARD COLOUR:

- White



ITEM	ID	OD	WALL		WORKING		BURSTING		BENDING		STANDARD		VACCUM		EX-STOCK	MOQ
			THICKNES	S	PRESSURE	PSI	PRESSURE	PSI	RADIUS	mm	WEIGHT	kg/mtr	LENGTH	mtr		
Code	mm	mm	mm		Bar	PSI	Bar	PSI	mm	kg/mtr	mtr	Bar	---		mtr	
FIRE38RL	38.00	-	-		8	120	24	360	-	-	30	-	YES		30	
FIRE50RL	50.00	-	-		8	120	24	360	-	-	30	-	YES		30	
FIRE63RL	63.00	-	-		8	120	24	360	-	-	30	-	YES		30	
FIRE75RL	75.00	-	-		8	120	24	360	-	-	30	-	YES		30	
FIRE100RL	100.00	-	-		8	120	24	360	-	-	30	-	YES		30	

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No. 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558