

TPE FLEXIBLE HOSE



TUBE:

- Thermo-Plastic Rubber (TPE)

REINFORCEMENT:

- Spring Steel Wire Integrated in Wall

COVER:

- Thermoplastic Rubber (TPE)

TEMP RANGE:

- -40 °C Approx. to +125 °C Approx.
- Short Time to +140 °C Approx

APPLICATIONS:

- For Gaseous Media Such As Vapors & Smoke
- For Steam Extraction
- As Conductor Of Hot & Cold Air
- For Blowers & Compressors

PROPERTIES:

- Good Resistance To Alkalis, Acids & Chemicals
- Capable Of Electrostatic Discharge By Grounding The Spiral.
- Small Bending Radius

STANDARD COLOUR:

- Black

MARKING ON THE HOSE:

Na



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11TPE50	50.00	58.00	-	0.27 -	- -	58	0.23	15	0.13	YES	5
11TPE63	63.00	71.00	-	0.21 -	- -	71	0.28	15	0.09	YES	5
11TPE76	76.00	84.00	-	0.18 -	- -	84	0.33	15	0.07	YES	5
11TPE100	100.00	108.00	-	0.14 -	- -	108	0.55	15	0.05	YES	5
11TPE125	125.00	133.00	-	0.11 -	- -	133	0.66	15	0.04	YES	5
11TPE150	150.00	158.00	-	0.09 -	- -	158	0.79	15	0.03	YES	5
11TPE203	203.00	211.00	-	0.06 -	- -	211	1.10	15	0.02	YES	5
11TPE254	254.00	262.00	-	0.04 -	- -	262	1.30	15	0.02	YES	5
11TPE305	305.00	313.00	-	0.01 -	- -	313	1.80	15	0.01	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No: 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558