


TUBE:

► Specially Compounded NBR Rubber, Black

REINFORCEMENT:

► Single Braided High Tensile Yarn

COVER:

► Black Abrasion Resistant Nitrile Rubber Cover

TEMP RANGE:

► -30°C Approx to +82°C Approx

APPLICATIONS:

► For All Heavy Duty use in Industrial Construction, Rock Drilling Mines, Crusher Zones & Other Rugged Conditions

PROPERTIES:

- Seamless
- Uniform Thickness
- Flexible
- High Abrasion Resistance

STANDARD COLOUR:

- Inner Tube - Black
- Outer Cover - Black

MARKING ON THE HOSE:

- Indo Maksson Super Rock Drill Hose
- Made in India

APPLICABLE STANDARDS:

- IS : 446 - Type III



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1RD12.5	12.50	21.00	4.25	25 360	75 1080	-	-	-	-	NO	200
1RD20	20.00	30.00	5.00	20 300	60 900	-	-	-	-	YES	5
1RD25	25.00	37.50	6.25	20 300	60 900	-	-	-	-	YES	5
1RD31.5	31.50	-	-	18 260	54 780	-	-	-	-	YES	5
1RD38	38.00	-	-	15 215	45 645	-	-	-	-	YES	5
1RD50	50.00	-	-	15 215	45 645	-	-	-	-	NO	40

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.