


TUBE:

- ▶ Smooth Plasticized PVC
- ▶ Smooth Interior

REINFORCEMENT:

- ▶ Fabric Reinforced

COVER:

- ▶ Smooth PVC Exterior Wall

TEMP RANGE:

- ▶ -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- ▶ Ideal For High Pressure Spraying of Pesticide (Water used Chemicals, Insecticides, Fungicides, Weeding etc).
- ▶ In Plantation Orchards Forestry Parks, Vineyards & Variety of Other Areas Involving Spraying by Hand Or Power Driven Pumps.

PROPERTIES:

- ▶ Optimized Flow Properties
- ▶ Small Bending Radius
- ▶ Long Service Life
- ▶ Strong Enough to withstand High Pressure, Total Consolidation & Adhesion Levels are Superb.

FEATURES:

- ▶ Light weight & Flexible
- ▶ Abrasion Resistant
- ▶ Crush & Kink Resistant

STANDARD COLOUR:

- ▶ Yellow

MARKING ON THE HOSE:

- ▶ Duplon Spray Hose Size... BP 150 Kg/cm²



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
2SSSB8.5	8.50	14.50	3.00	50 725	150 2175	-	-	100/200	-	YES	100
2SSSB10	10.00	16.00	3.00	50 725	150 2175	-	-	100/200	-	YES	100
2SSSB12	12.00	19.00	3.50	40 580	120 1740	-	-	100/200	-	YES	100

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.