


TUBE:

- Thin & Very Smooth plasticized PVC Wall
- Specially Compounded Rigid PVC

REINFORCEMENT:

- Reinforcement Which Is Helically Wound & Inseparably Fused To Soft Inner Walls

COVER:

- Wall: PVC

TEMP RANGE:

- -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- Cooling Of Motors & Air Intakes For All Types Of Machinery & Equipments.
- Conveying Warm Air For Drying Purposes
- Removing Fumes From Factories, Fuel Tanks & Underground Installations
- Transportation Of Powders, Gases & Liquids
- Collection Of Fibre Waste, Sawdust, Wood Shavings & Dust Collections of Metal Grinders

PROPERTIES:

- Strong Resistance To Most Chemicals, Acids & Alkalies.
- Abrasion Resistant, Crush Proof & Kink Proof.

STANDARD COLOUR:

- Transparent

MARKING ON THE HOSE:

- ASHISH REALFLEX DUCT HOSE (VACUUM)
MFG. AAPL (INDIA) CODE.....

FEATURES:

- Light Weight
- Highly Flexible



ITEM	ID	OD	WALL THICKNES S	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
4DUCT25TPT	25.40 ± 0.5	32.10 ± 0.5	3.35	- -	- -	45	0.31	30	-	NO	150
4DUCT30TPT	31.80 ± 0.5	38.64 ± 0.5	3.42	- -	- -	50	0.35	30	-	NO	90
4DUCT40TPT	38.00 ± 0.5	45.00 ± 0.5	3.50	- -	- -	55	0.42	30	-	YES	5
4DUCT50TPT	50.80 ± 0.5	58.20 ± 0.5	3.70	- -	- -	65	0.57	30	-	YES	5
4DUCT60TPT	60.50 ± 0.5	69.50 ± 0.5	4.50	- -	- -	75	0.63	30	-	YES	5
4DUCT63TPT	63.00 ± 0.5	72.00 ± 0.5	4.50	- -	- -	85	0.73	30	-	YES	5
4DUCT75TPT	76.50 ± 0.5	84.54 ± 0.5	4.02	- -	- -	95	0.80	30	-	YES	5
4DUCT80TPT	80.00 ± 0.5	89.00 ± 0.5	4.50	- -	- -	100	0.90	30	-	YES	5
4DUCT90TPT	90.00 ± 0.5	99.00 ± 0.5	4.50	- -	- -	110	1.03	30	-	NO	30
4DUCT100TPT	101.20 ± 0.5	111.94 ± 0.5	5.37	- -	- -	125	1.17	30	-	YES	5
4DUCT110TPT	110.00 ± 0.7	122.00 ± 0.7	6.00	- -	- -	125	1.33	30	-	NO	30
4DUCT125TPT	127.00 ± 0.7	137.20 ± 0.7	5.10	- -	- -	140	1.60	15	-	YES	5
4DUCT140TPT	140.00 ± 0.7	150.50 ± 0.7	5.25	- -	- -	150	1.80	15	-	NO	15
4DUCT150TPT	152.40 ± 0.7	163.10 ± 0.7	5.35	- -	- -	205	2.33	15	-	YES	5
4DUCT160TPT	160.40 ± 0.7	172.00 ± 0.7	5.80	- -	- -	210	2.66	15	-	NO	15
4DUCT200TPT	204.00 ± 1.5	216.40 ± 1.0	6.20	- -	- -	270	2.86	15	-	NO	15

Specification Subject to change due to Improvement in Quality (E&O.E).
 In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006
 Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No. 5020 0006647 423
 RTGS/NEFT IFSC:HDFC0000558