


TUBE:

- ▶ Smooth Plasticized PVC
- ▶ Smooth Interior

REINFORCEMENT:

- ▶ Fabric Reinforced

COVER:

- ▶ Smooth PVC Exterior Wall

TEMP RANGE:

- ▶ -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- ▶ For Heavy Duty Pneumatic Rock Drilling Applications in Quarries, Marble/Granite Mines, Drilling in Hard Services Like Road, Concrete etc.

PROPERTIES:

- ▶ Optimized Flow Properties
- ▶ Small Bending Radius
- ▶ Long Service Life
- ▶ Strong Enough to withstand High Pressure, Total Consolidation & Adhesion Levels are Superb.

FEATURES:

- ▶ Light weight & Flexible
- ▶ Abrasion Resistant
- ▶ Rodent Proof
- ▶ Crush & Kink Resistant

STANDARD COLOUR:

- ▶ Yellow

MARKING ON THE HOSE:

- ▶ Duplon Rock Drill Power Hose Size... BP...



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
2RD20	20.00	28.20	4.10	35	510	100	1530	-	-	60	-	YES	30
2RD25	25.00	35.00	5.00	30	435	90	1305	-	-	60	-	YES	100

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.