

TUBE:

► Synthetic Oil Resistant Rubber

REINFORCEMENT:

► Three High Tensile Steel Wire Braids

COVER:

► Synthetic Rubber

TEMP RANGE:

► -40°C Approx to +100°C Approx

APPLICATIONS:

- An Extra High Pressure Hose
- An Alternative to Multi Spiral Hose Where a Relatively Flexible And High Pressure Hose Is Required.

STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

 ► Size...333-IM-12 Extra High Pressure Hose ID...
 WP...Bar/PSI Flame Resistant


ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1VHP08	12.70	25.20	6.25	470	6815	1880	27260	160	-	-	-	NO	100
1VHP10	15.90	27.70	5.90	400	5800	1600	23200	216	-	-	-	NO	100
1VHP12	19.10	32.50	6.70	355	5148	1420	20590	262	-	-	-	NO	100
1VHP16	25.40	40.60	7.60	310	4495	1240	17980	318	-	-	-	NO	100

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.