

SUPER JACK HOSE



TUBE:

► Synthetic Oil Resistant Rubber

REINFORCEMENT:

► Two High Tensile Steel Wire Braids

COVER:

► Weather & Ozone Resistant Synthetic Rubber

TEMP RANGE:

► -40°C Approx to +50°C Approx

APPLICATIONS:

► Designed For Use In Hydraulic Jack Application
Used In Jacking Systems.

STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

► Size...Jack Hose Indo - Jack - 1M-4-Super
Jack Hose ID...WP...Bar/PSI



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1JACK04	6.40	14.80	4.20	690 10005	1380 20010	102	-	-	-	YES	5
1JACK06	9.50	18.80	4.65	690 10005	1380 20010	127	-	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).
In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.