


TUBE:

► PVC Coated Fibre

REINFORCEMENT:

► Plastic Coated Spring Steel Wire

COVER:

► Soft PVC with Fibre Reinforcement

TEMP RANGE:

► 0 °C Approx. to +85 °C Approx.

APPLICATIONS:

- Suction and Blast Hose, Especially Suitable:
For Solids such as Dust, Powder & Fibres
- For Gaseous & Liquid Media
- For Domestic & Industrial Vacuum Cleaners,
Building Drying & Welding Gas Extraction.

PROPERTIES:

- Light Model, Highly Flexible, Small Bending Radius & Kink-Proof.
- Good Resistance to Alkalis & Acids, UV & Ozone
- Capable of Electro-Static Discharge (Acc to BGR 132, Formerly ZH 1/200) by Grounding the Spiral).

STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

NA



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11PVCSP32	32.00	38.00	-	1.50 -	- -	32	0.28	15	0.20	NO	100
11PVCSP38	38.00	44.00	-	1.40 -	- -	38	0.34	15	0.20	YES	5
11PVCSP41	41.00	47.00	-	1.40 -	- -	41	0.37	15	0.18	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.