


STANDARD COLOUR:

► Black

TUBE:

► Synthetic Oil Resistant Rubber

REINFORCEMENT:

► One Braid of High Tensile Steel Wire Over One Braid of Textile.

COVER:

► Weather & Oil Resistant Synthetic Rubber

TEMP RANGE:

► -40°C Approx to +100°C Approx

APPLICATIONS:

► Medium Pressure Hydraulic Oil Lines

APPLICABLE STANDARDS:

► As Per SAE 100 R5



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDAR	VACCUM	EX-STOCK	MOQ
				Bar	PSI	Bar	PSI			D LENGTH	PRESSURE		
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1R5R03	4.80	13.20	4.20	210	3045	840	12180	76	-	-	-	NO	50
1R5R04	6.40	14.80	4.20	210	3045	840	12180	86	-	-	-	NO	50
1R5R05	7.90	17.20	4.65	157	2277	628	9106	101	-	-	-	NO	50
1R5R06	10.30	19.50	4.60	140	2030	560	8120	117	-	-	-	NO	50
1R5R08	12.70	23.40	5.35	122	1769	488	7076	140	-	-	-	NO	50
1R5R10	15.90	27.40	5.75	105	1522	420	6090	165	-	-	-	NO	50
1R5R14	22.20	31.40	4.60	56	812	224	3248	188	-	-	-	NO	50
1R5R18	28.60	38.10	4.75	43	624	172	2494	229	-	-	-	NO	50
1R5R22	34.90	44.50	4.80	35	508	140	2030	267	-	-	-	NO	50
1R5R29	46.00	58.90	6.45	24	348	96	1392	338	-	-	-	NO	50

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.