

TUBE:

► EPDM Rubber Resistant to Saturated Steam

REINFORCEMENT:

► High Tensile Textile Plies

COVER:

► Black, Smooth, Weather, Abrasion, Heat, Steam & Ozone Resistant Pin Pricked Special Synthetic Rubber.

► Fabric Impression

TEMP RANGE:

► -40°C Approx to +165°C Approx

APPLICATIONS:

► For General Saturated Steam Services
 ► For Cleaning & Sterilization with Steam

PROPERTIES:

► Seamless
 ► Uniform Thickness
 ► Smooth Bore
 ► Mandrel Built

STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

► Stream Line Steam Hose Made in India

APPLICABLE STANDARDS:

► IS : 5122/1975 Type II



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1STM12.5	12.00	22.00	5.00	7	100	70	1000	-	-	-	-	YES	5
1STM20	20.00	31.00	5.50	7	100	70	1000	-	-	-	-	YES	5
1STM25	25.00	38.00	6.50	7	100	70	1000	-	-	-	-	YES	5
1STM31.5	31.00	44.00	6.50	7	100	70	1000	-	-	-	-	YES	5
1STM38	38.00	52.00	7.00	7	100	70	1000	-	-	-	-	YES	5
1STM50	50.00	66.00	8.00	7	100	70	1000	-	-	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.