

SAND BLAST HOSE



TUBE:

- Black, Smooth, Natural and Synthetic Rubber Resistant to Abrasion.

REINFORCEMENT:

- High Tensile Textile Plies with Anti Static Copper Wire.

COVER:

- Black, Smooth, Weather & Abrasion Resistant Rubber.
- Fabric Impression

TEMP RANGE:

- -40°C Approx to +70°C Approx

APPLICATIONS:

- Abrasion Resistant Sand, Corundum, Shot & Grit Blast Delivery Hose normally used for surface treatment.
- For Cleaning & Blasting Metal, Stone & Concrete Surfaces.

PROPERTIES:

- Seamless
- Uniform Thickness
- Smooth Bore
- Mandrel Built

FEATURES:

- Highly Abrasion Resistant Rubber Tube
- Anti Static Copper Wire Embedded in the Hose

STANDARD COLOUR:

- Black

MARKING ON THE HOSE:

- Sand Blast Hose IS 5894/90 WP 10 kg/cm² Made in India

APPLICABLE STANDARDS:

- IS: 5894/90



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1SBL10KG12.5	12.50	-	-	10 145	30 435	-	-	-	-	NO	100
1SBL10KG20	20.00	-	-	10 145	30 435	-	1.00	-	-	YES	5
1SBL10KG25	25.00	-	-	10 145	30 435	-	1.30	-	-	YES	5
1SBL10KG31.5	31.50	-	-	10 145	30 435	-	1.74	-	-	NO	100
1SBL10KG38	38.00	-	-	10 145	30 435	-	1.90	-	-	NO	100

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No: 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558