


TUBE:

► Poly Propylene

REINFORCEMENT:

► Spring Steel Wire Integrated in Wall

COVER:

► Heavily Corrugated & Capable of Axial Compression into fixed position

TEMP RANGE:

► -20 °C Approx. to +80 °C Approx.

APPLICATIONS:

 ► Vent Ducts Requiring Flexible & Free-Bending Lengths
 ► Ventilation for various kinds of Equipments

PROPERTIES:

 ► Super Light Model
 ► Good Resistance To Alkalis & Acids
 ► Good Resistance To Chemicals
 ► Good Resistance To UV & Ozone

STANDARD COLOUR:

► Ivory

MARKING ON THE HOSE:

NA

FEATURES:

► Self Supporting


 WALL
THICKNESS

ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11PP25	25.00	32.00	-	0.70 -	- -	35	0.10	5	0.25	YES	5
11PP32	32.00	38.00	-	0.65 -	- -	42	0.13	5	0.22	YES	5
11PP38	38.00	46.00	-	0.58 -	- -	50	0.15	5	0.19	YES	5
11PP50	50.00	58.00	-	0.43 -	- -	64	0.19	5	0.16	YES	5
11PP63	63.00	73.00	-	0.35 -	- -	80	0.24	5	0.12	YES	5
11PP76	76.00	85.00	-	0.30 -	- -	93	0.30	5	0.10	YES	5
11PP90	90.00	100.00	-	0.25 -	- -	110	0.36	5	0.07	YES	5
11PP100	100.00	110.00	-	0.23 -	- -	120	0.40	5	0.06	YES	5
11PP125	125.00	135.00	-	0.18 -	- -	148	0.52	5	0.04	YES	5
11PP150	150.00	160.00	-	0.16 -	- -	176	0.80	5	0.04	YES	5
11PP200	200.00	210.00	-	0.12 -	- -	230	1.10	5	0.03	YES	5
11PP250	250.00	260.00	-	0.09 -	- -	286	1.56	5	0.01	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.