


**TUBE:**

- Strong, Flexible & Smooth Plasticized PVC
- Shock Resistant Hard Rigid PVC Spiral

**REINFORCEMENT:**

- Hard Rigid PVC Spiral

**COVER:**

- Hard Rigid PVC

**TEMP RANGE:**

- -10 °C Approx. To +70 °C Approx.

**APPLICATIONS:**

- Strongly Recommended For Conveying Diesel Fuels, Kerosene Liquid Petroleum Products, Lubricating Oil, Mineral Oils, Light Oils, Transformer etc.

**PROPERTIES:**

- Resistant To Oil & Other Chemicals.
- Resistant To Absolute Vacuum, Easy To Handle.
- Quite Tough: Tough Enough To Resist Distortion Under Impact & Crush Loads During Service.

**FEATURES:**

- Flexibility: Specially Designed To Have Greater Flexibility Than Rubber & Hose Can Be Bent As Desired In Practical Uses.
- Smooth Inside Surface Results In Quick Conveyance Of Fluids, This Means Minimum Friction Loss, Saves Higher Energy & High Flow Rate.

**STANDARD COLOUR:**

- Blue

**MARKING ON THE HOSE:**

- Oil Hose India



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
2OIL25	25.40 ± 0.5	31.50 ± 1.0	3.05	8 115	22 315	48	-	30	-	NO	30
2OIL30	31.80 ± 0.5	39.00 ± 1.0	3.60	7 100	21 300	68	-	30	-	NO	30
2OIL40	38.10 ± 0.5	46.40 ± 1.0	4.15	5.5 80	18 260	70	-	30	-	NO	30
2OIL50	50.80 ± 0.5	60.80 ± 1.5	5.00	4.5 65	18 260	100	-	30	-	NO	30
2OIL65	63.50 ± 1.0	74.50 ± 1.5	5.50	4.5 65	18 260	120	-	30	-	NO	30
2OIL75	76.20 ± 1.0	87.20 ± 1.5	5.50	4.5 65	18 260	155	-	30	-	NO	30
2OIL100	101.20 ± 1.0	114.20 ± 1.5	6.50	4 60	14 200	213	-	30	-	NO	30

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

**LALIT MACHINERY STORE**

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

**BANK DETAILS**

HDFC Bank A/c No. 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558