

FABRIC HD HOSE



TUBE:

- Fabric Reinforced Tape

REINFORCEMENT:

- Spring Steel Wire Integrated in Wall

COVER:

- PVC Coated Polyester Fabric

TEMP RANGE:

- -10 °C Approx. to +80 °C Approx.
- Short Time to +100 °C Approx.

APPLICATIONS:

- For Welding Gas Extraction
- For Air Conditioning & Ventilation Technology

PROPERTIES:

- Good Resistance To Alkalis & Acids, Chemicals, UV & Ozone.
- Highly Flexible & Compressible 6:1
- Capable Of Electro-Static Discharge By Grounding The Spiral.
- Flame-Retardant Acc To UL94-HB

STANDARD COLOUR:

- Black, Blue & Grey

MARKING ON THE HOSE:

NA



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11FBHD76	76.00	85.00	0.35	0.16 2.32	- -	85	0.23	10	0.08	YES	10
11FBHD100	100.00	109.00	0.35	0.12 1.74	- -	109	0.32	10	0.05	YES	10
11FBHD125	125.00	134.00	0.35	0.10 1.45	- -	134	0.42	10	0.04	YES	10
11FBHD150	150.00	159.00	0.35	0.08 1.16	- -	159	0.55	10	0.03	YES	10
11FBHD203	203.00	212.00	0.35	0.06 0.87	- -	212	0.86	10	0.02	YES	10
11FBHD254	254.00	263.00	0.35	0.05 0.73	- -	263	1.20	10	0.01	YES	10
11FBHD305	305.00	314.00	0.35	0.04 0.58	- -	314	1.30	10	0.01	YES	10

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.