


TUBE:

► Synthetic Rubber Tube, EPDM, Black or White

REINFORCEMENT:

► Braided High Tensile Yarn

COVER:

► Perforated Synthetic Rubber Cover, EPDM

TEMP RANGE:

► -30°C Approx to +100°C Approx

APPLICATIONS:

► For Conveyance of Wide Range of Chemicals
Such as Acid, Alkalies Inorganic In Salt &
Alcoholic Materials

PROPERTIES:

► Chemical Resistant
► Uniform Thickness
► Flexible

STANDARD COLOUR:

► Inner Tube - Black or White
► Outer Cover - Black

MARKING ON THE HOSE:

► Indo Maksson Multi Purpose Chemical Hose
Made in India

APPLICABLE STANDARDS:

► IS : 7654/1975 Type I

ITEM Code	ID mm	OD mm	WALL THICKNES S mm	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS mm	WEIGHT Kg/mtr	STANDAR D LENGTH mtr	VACCUM PRESSURE Bar	EX-STOCK ---	MOQ mtr
				Bar	PSI	Bar	PSI						
1CHL12.5	12.50	-	-	12	170	48	700	-	-	-	-	NO	200
1CHL20	19.00	31.00	6.00	12	170	48	700	152	-	-	-	YES	5
1CHL25	25.00	38.00	6.50	12	170	48	700	203	-	-	-	YES	5
1CHL31.5	31.00	45.00	7.00	12	170	48	700	215	-	-	-	YES	5
1CHL38	38.00	52.00	7.00	12	170	48	700	254	-	-	-	YES	5
1CHL50	50.00	68.00	9.00	12	170	48	700	355	-	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.