


TUBE:

► Specially Compounded Synthetic Rubber, Black

REINFORCEMENT:

► Braiding of High Strength Synthetic Fibre

COVER:

► Black Synthetic Rubber Cover

TEMPERATURE RANGE:

► -40°C Approx to +70°C Approx

APPLICATIONS:

► For All Air & Water Applications that Require Seamless Conveyance in any Industry

PROPERTIES:

- Seamless
- Uniform Thickness
- Flexible

STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

► Indo Maksson Heavy Duty Water/Air Hose
Made in India

APPLICABLE STANDARDS:

► IS : 444 - Type I & Type II

ITEM Code	ID mm	OD mm	WALL THICKNES S mm	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS mm	WEIGHT Kg/mtr	STANDAR D LENGTH mtr	VACCUM PRESSURE Bar	EX-STOCK ---	MOQ mtr
				Bar	PSI	Bar	PSI						
1WTR12.5	12.00	22.00	5.00	12	170	36	510	127	0.36	-	-	YES	5
1WTR20	20.00	29.50	4.75	12	170	36	510	152	0.58	-	-	YES	5
1WTR25	25.00	37.00	6.00	12	170	36	510	203	0.77	-	-	YES	5
1WTR31.5	31.00	43.50	6.25	12	170	36	510	254	1.00	-	-	YES	5
1WTR38	38.00	51.50	6.75	12	170	36	510	304	1.20	-	-	YES	5
1WTR50	50.00	65.00	7.50	12	170	36	510	419	1.80	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.