


**TUBE:**

- PVC Compound Resistant to Pesticides & Fertilizers
- Smooth Interior Wall

**REINFORCEMENT:**

- Fabric Reinforced

**COVER:**

- PVC Exterior Wall

**TEMP RANGE:**

- -10 °C Approx. To +70 °C Approx.

**APPLICATIONS:**

- Ideal For High Pressure Spraying of Pesticide (Water based Chemicals, Insecticides, Fungicides, Weeding etc)
- In Plantation Orchards Forestry Parks, Vineyards & Variety of Other Areas Involving Spraying by Hand Or Power Driven Pumps.

**PROPERTIES:**

- Optimized Flow Properties
- Small Bending Radius
- Long Service Life
- Strong Enough to withstand High Pressure, Total Consolidation & Adhesion Levels are Superb.

**FEATURES:**

- Light weight & Flexible
- Abrasion Resistant
- Crush & Kink Resistant

**STANDARD COLOUR:**

- Yellow

**MARKING ON THE HOSE:**

- Dunlop Power Spray Hose Size..  
Wp 50k Bp 150k Mfg Sel



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
3SSSB8.5	8.50	14.50	3.00	50 725	150 2175	-	-	100	-	YES	5
3SSSB10	9.50	16.00	3.25	50 725	150 2175	-	-	100	-	YES	5
3SSSB12	12.50	20.00	3.75	40 580	120 1740	-	-	100	-	YES	5

Specification Subject to Change Due to Improvement in Quality (E & O.E).

In the Interest of Continual development, The company Reserves The Right to Make Modifications to These Details Without Prior Notice.