


STANDARD COLOUR:

- Grey

MARKING ON THE HOSE:

- Ashish Realflex Duct Hose (Vacuum) Mfg AAPL (India) Code...

TUBE:

- Thin & Very Smooth plasticized PVC Wall
- Specially Compounded Rigid PVC

REINFORCEMENT:

- Reinforcement which is Helically Wound & Inseparably Fused To Soft Inner Walls

COVER:

- Wall: PVC

TEMP RANGE:

- -10°C to + 70°C Approx

APPLICATIONS:

- Cold Or Warm Air Installations Of Various Kinds.
- Cooling Of Motors & Air Intakes For All Types Of Machinery & Equipments.
- Conveying Warm Air For Drying Purposes.
- Removing Fumes From Factories, Fuel Tanks & Underground Installations.

PROPERTIES:

- Strong Resistance To Most Chemicals, Acids & Alkalies.
- Abrasion Resistant
- Crush Proof & Kink Proof

FEATURES:

- Light Weight
- Highly Flexible


STANDAR

ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	D LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ		
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
4DUCT16	15.90 ± 1.0	24.00 ± 1.0	4.05	-	-	-	-	40	0.19	30	-	YES	30
4DUCT22	21.00 ± 0.5	26.60 ± 0.5	2.80	-	-	-	-	35	0.24	30	-	YES	30
4DUCT25	25.40 ± 0.5	32.10 ± 0.5	3.35	-	-	-	-	45	0.31	30	-	YES	30
4DUCT30	31.80 ± 0.5	38.64 ± 0.5	3.42	-	-	-	-	50	0.35	30	-	YES	30
4DUCT40	38.00 ± 0.5	45.00 ± 0.5	3.50	-	-	-	-	55	0.42	30	-	YES	5
4DUCT50	50.80 ± 0.5	58.20 ± 0.5	3.70	-	-	-	-	65	0.57	30	-	YES	5
4DUCT60	60.50 ± 0.5	69.50 ± 0.5	4.50	-	-	-	-	75	0.63	30	-	NO	30
4DUCT63	63.00 ± 0.5	72.00 ± 0.5	4.50	-	-	-	-	85	0.73	30	-	YES	5
4DUCT75	76.50 ± 0.5	84.54 ± 0.5	4.02	-	-	-	-	95	0.80	30	-	YES	5
4DUCT80	80.00 ± 0.5	89.00 ± 0.5	4.50	-	-	-	-	100	0.90	30	-	NO	30
4DUCT90	90.00 ± 0.5	99.00 ± 0.5	4.50	-	-	-	-	110	1.03	30	-	YES	30
4DUCT100	101.20 ± 0.5	111.94 ± 0.5	5.37	-	-	-	-	125	1.17	30	-	YES	5
4DUCT110	110.00 ± 0.7	122.00 ± 0.7	6.00	-	-	-	-	125	1.33	30	-	NO	30
4DUCT125	127.00 ± 0.7	137.20 ± 0.7	5.10	-	-	-	-	140	1.60	15	-	YES	5
4DUCT140	140.00 ± 0.7	150.50 ± 0.7	5.25	-	-	-	-	150	1.80	15	-	NO	15
4DUCT150	152.40 ± 0.7	163.10 ± 0.7	5.35	-	-	-	-	205	2.33	15	-	YES	5
4DUCT160	160.40 ± 0.7	172.00 ± 0.7	5.80	-	-	-	-	210	2.66	15	-	NO	15
4DUCT200	204.00 ± 1.5	216.40 ± 1.0	6.20	-	-	-	-	270	2.86	15	-	YES	5
4DUCT225	225.00 ± 1.5	239.00 ± 1.0	7.00	-	-	-	-	350	3.33	15	-	NO	15
4DUCT250	253.00 ± 1.5	266.00 ± 1.0	6.50	-	-	-	-	370	5.00	10	-	YES	5
4DUCT300	305.00 ± 1.5	321.00 ± 1.0	8.00	-	-	-	-	470	6.50	10	-	NO	10

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No. 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558