


TUBE:

- ▶ Black Plasticized PVC
- ▶ Smooth Interior

REINFORCEMENT:

- ▶ Fabric Reinforced

COVER:

- ▶ Smooth PVC Exterior Wall

TEMP RANGE:

- ▶ -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- ▶ Ideal for Conveying of Water for Engineering, Construction & Industrial Development Work.

PROPERTIES:

- ▶ Optimized Flow Properties
- ▶ Small Bending Radius
- ▶ Long Service Life

FEATURES:

- ▶ Light weight & Flexible
- ▶ Abrasion Resistant
- ▶ Crush & Kink Resistant
- ▶ UV Resistant

STANDARD COLOUR:

- ▶ Outer Cover Yellow

MARKING ON THE HOSE:

- ▶ Construction Water Hose Size...



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/Coil	mtr	Bar	---	Coils
2CWTR1230	12.00	16.00	2.00	7	100	21	300	-	-	30	-	NO	6
2CWTR1250	12.00	16.00	2.00	7	100	21	300	-	-	50	-	NO	6
2CWTR2030	20.00	25.00	2.50	7	100	21	300	-	-	30	-	NO	6
2CWTR2050	20.00	25.00	2.50	7	100	21	300	-	-	50	-	NO	5
2CWTR2530	25.00	31.00	3.00	5	75	15	225	-	-	30	-	NO	5
2CWTR2550	25.00	31.00	3.00	5	75	15	225	-	-	30	-	NO	3
2CWTR3030	30.00	37.60	3.80	5	75	15	225	-	-	30	-	NO	2
2CWTR3050	30.00	37.60	3.80	5	75	15	225	-	-	50	-	NO	1
2CWTR4030	38.10	48.10	5.00	5	75	15	225	-	-	30	-	NO	1
2CWTR4050	38.10	48.10	5.00	5	75	15	225	-	-	50	-	NO	1
2CWTR5030	50.80	62.80	6.00	5	75	15	225	-	-	30	-	NO	1
2CWTR5050	50.80	62.80	6.00	5	75	15	225	-	-	50	-	NO	1

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.