


TUBE:

- Smooth Plastcized PVC
- Smooth Interior

REINFORCEMENT:

- Fabric Reinforced

COVER:

- Smooth PVC Exterior Wall

TEMP RANGE:

- -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- Multipurpose Hose for Air, Pneumatic, Heavy Duty Suction & Delivery of Water & Chemicals.

PROPERTIES:

- Optimized Flow Properties
- Good Resistance To Alkali, Acids, UV, Ozone, Oil, Chemicals & Moisture.
- Gas & Liquid Tight
- Crush-Proof & Kink Resistant

FEATURES:

- Highly Flexible
- Small Bending Radius
- Abrasion Resistant
- Strong Enough To Withstand High Pressure, Total Consolidation & Adhesion Levels Are Superb.

STANDARD COLOUR:

- Transparent

MARKING ON THE HOSE:

- Duplon Hose Size.... WP

APPLICABLE STANDARDS:

- In Line with BIS Standards



ITEM	ID	OD	WALL		WORKING		BURSTING		BENDING	WEIGHT	STANDARD		VACCUM	EX-STOCK	MOQ
			THICKNES	S	PRESSURE	PSI	PRESSURE	PSI			RADIUS	LENGTH	PRESSURE		
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr		
2BR5	5.00	10.00	2.50	15	220	45	660	-	-	100/200	-	YES	100		
2BR6	6.00	12.00	3.00	25	360	75	1080	-	-	100	-	YES	100		
2BR8	8.00	14.00	3.00	25	360	75	1080	-	-	100	-	YES	100		
2BR10	10.00	17.00	3.50	25	360	75	1080	-	-	100	-	YES	100		
2BR12	12.00	19.00	3.50	20	290	60	870	-	-	100	-	YES	100		
2BR15	15.00	22.00	3.50	20	290	60	870	-	-	100	-	YES	100		
2BR20	20.00	28.00	4.00	20	290	60	870	-	-	100/200	-	YES	100		
2BR25	25.00	34.60	4.80	15	220	45	660	-	-	100	-	YES	100		
2BR30	30.00	39.60	4.80	15	220	45	660	-	-	50/100	-	YES	50		
2BR40	40.00	50.00	5.00	15	220	45	660	-	-	50	-	YES	50		
2BR50	50.00	62.00	6.00	10	145	30	435	-	-	50	-	YES	50		
2BR65	63.50	77.50	7.00	7	100	22	300	-	-	15	-	No	15		
2BR75	75.80	92.80	8.50	6	85	18	255	-	-	15	-	No	15		

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No. 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558