


STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

► ...MM R2 INDO-2AT-IM-...HIGH IMPULSE
 DIN EN 853-2SN ID...MAX WP...BAR/...PSI
 (EXCEEDS SAE 100 R2 AT) FLAME RESISTANT

TUBE:

► Synthetic Oil Resistant Rubber

REINFORCEMENT

► Two High Tensile Steel Wire Braids

COVER:

► Black, Weather & Oil Resistant Synthetic Rubber
 ► Upto 19mm - Smooth Finish & 25mm onwards
 Fabric Impression.

TEMP RANGE:

► -40°C Approx to +100°C Approx
 (+120°C Intermittent)

APPLICATIONS:

► High Pressure Hydraulic Lines

APPLICABLE STANDARDS:

► SAE 100 R2 AT (DIN EN 853 2SN)



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1R204	6.40	15.00	4.30	400	5800	1600	23200	100	0.35	-	-	YES	5
1R205	7.90	16.60	4.35	350	5075	1400	20300	115	0.40	-	-	YES	5
1R206	9.50	19.00	4.75	330	4785	1320	19140	127	0.50	-	-	YES	5
1R208	12.70	22.20	4.75	275	3988	1100	15950	178	0.65	-	-	YES	5
1R210	15.90	25.40	4.75	250	3625	1000	14500	200	0.80	-	-	YES	5
1R212	19.10	29.30	5.10	215	3118	860	12470	241	0.94	-	-	YES	5
1R216	25.40	38.10	6.35	165	2393	660	9570	300	1.36	-	-	YES	5
1R220	31.80	48.30	8.25	125	1813	500	7250	420	1.90	-	-	YES	5
1R224	38.10	54.60	8.25	90	1305	360	5220	500	2.30	-	-	YES	5
1R232	50.80	67.30	8.25	80	1160	320	4640	635	2.95	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.