


TUBE:

► Synthetic Oil Resistant Rubber

REINFORCEMENT:

► Two Textile Braid

COVER:

► Weather & Oil Resistant Synthetic Rubber

TEMP RANGE:

► -40°C Approx to +100°C Approx

APPLICATIONS:

► Medium Pressure Hydraulic Oil Lines

STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

► SIZE...R3 Indo 3-lm-24 DIN EN 854 ID...

WP...Bar/PSI (Exceeds SAE 100 R3)

APPLICABLE STANDARDS:

► SAE 100 R3 (DIN EN 854)



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1R304	6.40	14.30	3.95	87	1250	348	5046	76	0.16	-	-	YES	5
1R305	7.90	17.50	4.80	84	1218	336	4872	101	0.24	-	-	YES	5
1R306	9.50	19.10	4.80	78	1131	312	4524	101	0.28	-	-	YES	5
1R308	12.70	23.80	5.55	70	1015	280	4060	127	0.38	-	-	YES	5
1R310	15.90	27.00	5.55	61	885	244	3538	140	0.45	-	-	NO	100
1R312	19.10	31.80	6.35	52	754	208	3016	152	0.63	-	-	YES	5
1R316	25.40	38.10	6.35	39	566	156	2250	203	0.75	-	-	YES	5
1R320	31.80	44.50	6.35	26	377	104	1500	254	0.97	-	-	YES	5
1R324	38.10	50.80	6.35	17	247	68	986	305	1.23	-	-	YES	5
1R332	50.80	64.00	6.60	15	218	60	870	409	-	-	-	NO	100

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.