


TUBE:

► Synthetic Oil Resistant Rubber

REINFORCEMENT:

► One Textile Braid

COVER:

► Weather & Oil Resistant Synthetic Rubber

TEMP RANGE:

► -40°C Approx to +100°C Approx

APPLICATIONS:

► Low Pressure Hydraulic Oil Lines

STANDARD COLOUR:

► Black

MARKING ON THE HOSE:

 ► Size...R6 Indo 6-IM-5 DIN EN 854 ID...
 WP...Bar/PSI (Exceeds SAE 100 R6)

APPLICABLE STANDARDS:

► SAE 100 R6 (DIN EN 854)



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1R604	6.40	12.70	3.15	28	406	112	1624	64	0.13	-	-	YES	5
1R605	7.90	14.30	3.20	28	406	112	1624	76	0.15	-	-	YES	5
1R606	9.50	16.00	3.25	28	406	112	1624	76	0.18	-	-	YES	5
1R608	12.70	19.80	3.55	28	406	112	1624	101	0.23	-	-	YES	5
1R610	15.90	23.10	3.60	24	348	96	1392	127	0.32	-	-	YES	5
1R612	19.10	26.60	3.75	21	305	84	1218	152	0.43	-	-	YES	5
1R616	25.40	32.50	3.55	15	210	60	870	178	0.50	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.