


TUBE:

- Flexible Smooth Plasticized PVC
- Inner Surface Smooth Highly Flexible

REINFORCEMENT:

- Synthetic Yarn Reinforcement

COVER:

- Smooth Plasticized PVC

TEMP RANGE:

- -10 °C Approx. To +70 °C Approx.

APPLICATIONS:

- In Agriculture Use Mainly As Delivery Hose
- At Construction Sites, Mines & Quarries, Flushing Is Faster With ItlinFlex Flat Hose.
- For Transferring Corrosive Chemicals & Liquids In Chemical Factories.
- Ideal For Use As Drainage Hose In Emergency / Flood / Disaster Situations When Large Quantities Of Water Must Be Moved Quickly.

PROPERTIES:

- Tough & Puncture Proof. Can resist External Pressure & Abrasion In Use Gives A Long Service Life.
- Can Carry Water / Liquids In Higher Heads & In Hilly Areas Without Inflation.

FEATURES:

- Requires No Maintenance .Do Not Rust Corrode Or Require Cathodic Protection.
- Roll Up Easily, Requires Minimum Storage Space and is Light Weight Too.
- Remains Soft & Pliable Even In Extremely Cold Weather & At Below Freezing Temperature.

STANDARD COLOUR:

- Blue

MARKING ON THE HOSE:

- Itlinflex Lay Flat Delivery Hose Size...WP...Mfg AAPL (India) Code...1 mtr



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
4FLAT25	26.00 ± .25	27.60 ± .25	0.80	4.00 60	12.00 180	-	-	100	-	No	500
4FLAT32	32.50 ± .25	34.30 ± .25	0.90	4.00 60	12.00 180	-	-	100	-	No	500
4FLAT38	40.00 ± .25	42.00 ± .25	1.00	4.00 60	12.00 180	-	-	100	-	No	300
4FLAT50	52.00 ± .50	54.20 ± .50	1.10	4.00 60	12.00 180	-	0.22	100	-	YES	100
4FLAT65	65.00 ± .65	67.40 ± .65	1.20	3.50 50	10.50 150	-	0.31	100	-	YES	100
4FLAT75	76.50 ± .75	78.90 ± .75	1.20	3.50 50	10.50 150	-	0.36	100	-	YES	100
4FLAT100	102.50 ± 1.0	104.90 ± 1.0	1.20	3.00 45	9.00 135	-	0.51	100	-	YES	100
4FLAT150	153.50 ± 1.2	156.50 ± 1.2	1.50	3.00 45	9.00 135	-	1.00	100	-	YES	100
4FLAT200	202.50 ± 1.2	206.10 ± 1.2	1.80	2.50 35	7.50 110	-	1.75	50	-	YES	50

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No. 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558