

TUBE:

- Specially Compounded Abrasion Resistant Natural Rubber, High Resilient

REINFORCEMENT:

- High Tensile Synthetic Plies With Helix Wire & Copper Wire

COVER:

- Black Abrasion Resistant Natural Rubber Cover Wrap Finish

TEMP RANGE:

- -40°C to +70°C Approx

APPLICATIONS:

- For Suction & Discharge of Bulk Material Like Cement, Gravel & Sand etc in Construction Industry

FEATURES:

- High Abrasion Resistance
- Seamless
- Uniform Thickness
- Flexible

STANDARD COLOUR:

- Inner Tube - Black
- Outer Cover - Black

MARKING ON THE HOSE:

- Indo-Makssson Toughline - Slurry Suction Hose I.D. W.P India

APPLICABLE STANDARDS:

- Indo Makssson Proprietary

													
ITEM	ID	OD	THICKNES S	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCU PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1SLSUC50	50.00	64.00	7.00	10	150	30	435	310		40		No	40
1SLSUC63	63.00	78.00	7.50	10	150	30	435	380		40		YES	5
1SLSUC75	75.00	91.00	8.00	10	150	30	435	460		40		YES	5
1SLSUC100	100.00	119.00	9.50	10	150	30	435	610		40		YES	5
1SLSUC125	125.00	146.00	10.50	10	150	30	435	760		40		YES	5
1SLSUC150	150.00	173.00	11.50	10	150	30	435	920		40		YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).
 In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.