


TUBE:

- Synthetic NBR Rubber, Resistant to Oil Mist Mixed Air & Inert Fluids.

REINFORCEMENT:

- High Tensile Steel Wire

COVER:

- Black, Smooth, Weather & Abrasion Resistant Pin Pricked Synthetic Rubber.
- Fabric Impression

TEMP RANGE:

- -30°C Approx to +80°C Approx

APPLICATIONS:

- Heavy Duty Service for Air specially in Mines, Quarries & Constructions.
- Suitable for Air with Oil Mist, for Compressors, Bore & Pneumatic Machines.

PROPERTIES:

- Seamless
- Uniform Thickness
- Smooth Bore
- Mandrel Built

STANDARD COLOUR:

- Black

MARKING ON THE HOSE:

- Super Dynamic Rock Drill Hose Oil/Abrasion Resistant WP...PSI

APPLICABLE STANDARDS:

- IS : 446/1987 Type III(HD)



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1RDWB12.5	12.50	-	-	60 870	240 3480	-	-	-	-	NO	200
1RDWB20	20.00	27.50	3.75	60 870	240 3480	152	-	-	-	YES	5
1RDWB25	25.00	36.50	5.75	50 725	200 2900	201	-	-	-	YES	5
1RDWB31.5	31.00	44.00	6.50	50 725	200 2900	254	-	-	-	YES	5
1RDWB38	38.00	50.00	6.00	50 725	200 2900	304	-	-	-	YES	5
1RDWB50	50.00	63.50	6.75	40 580	160 2320	355	-	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.