


TUBE:

- ▶ Silicone Coated Glass Fabric
- ▶ Fabric-Reinforced Tape

REINFORCEMENT:

- ▶ Spring Steel Wire Integrated in Wall
- ▶ Cord As Reinforcement

COVER:

- ▶ Spiral Yarn Fixing

TEMP RANGE:

- ▶ -70 °C Approx. to +260 °C Approx.
- ▶ Short Time to +280 °C Approx.

APPLICATIONS:

- ▶ As Conductor Of Hot & Cold Air
- ▶ For Granulate Dryers In The Plastic Industry
- ▶ For Printing Machines, Blowers & Compressors
- ▶ For Exhaust Gas Technology, Engine Construction & Engine Warming.

PROPERTIES:

- ▶ Very Good Heat Resistance
- ▶ Double-Layer, Leak-Proof, Smooth Interior, Fibre Reinforced, Kink-Proof & Small Bending Radius.
- ▶ Flame-Retardant Acc To UL94-HB

STANDARD COLOUR:

- ▶ Red

MARKING ON THE HOSE:

- ▶ NA



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
501SIL25	25.00	30.00	-	2.75 -	- -	44	0.13	4	0.71	YES	4
501SIL32	32.00	37.00	-	2.70 -	- -	54	0.15	4	0.65	YES	4
501SIL40	40.00	45.00	-	2.70 -	- -	64	0.20	4	0.60	YES	4
501SIL44	44.00	49.00	-	2.55 -	- -	70	0.24	4	0.58	YES	4
501SIL51	51.00	57.00	-	2.55 -	- -	85	0.27	4	0.52	YES	4
501SIL63	63.00	69.00	-	2.35 -	- -	102	0.35	4	0.46	YES	4
501SIL76	76.00	82.00	-	2.15 -	- -	122	0.41	4	0.43	YES	4
501SIL84	84.00	90.00	-	2.05 -	- -	130	0.44	4	0.43	YES	4
501SIL89	90.00	96.00	-	2.05 -	- -	141	0.46	4	0.40	YES	4
501SIL100	102.00	108.00	-	2.00 -	- -	161	0.48	4	0.35	YES	4
501SIL114	115.00	120.00	-	1.80 -	- -	180	0.55	4	0.30	YES	4
501SIL127	127.00	134.00	-	1.50 -	- -	200	0.65	4	0.23	YES	4
501SIL150	152.00	158.00	-	1.30 -	- -	237	0.80	4	0.17	YES	4
501SIL165	160.00	167.00	-	1.20 -	- -	258	0.88	4	0.14	YES	4
501SIL175	175.00	182.00	-	1.05 -	- -	277	1.13	4	0.12	YES	4
501SIL203	203.00	209.00	-	0.90 -	- -	313	1.30	4	0.09	YES	4
501SIL254	254.00	261.00	-	0.75 -	- -	390	1.50	4	0.07	YES	4
501SIL305	305.00	312.00	-	0.65 -	- -	467	1.60	4	0.07	YES	4

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No: 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558