

RIGID BEND PVC DUCT HOSE





► Rigid PVC

REINFORCEMENT:

► Interlocking Rigid PVC Profile

COVER:

▶PVC

TEMP RANGE:

▶-10 °C Approx. to +70 °C Approx.

APPLICATIONS:

- ► For Air, Fume Extraction & Liquid Supply Under Low Pressure.
- ► For Conveyance Of Powders, Granules & Dust Extraction.
- ► For Woodworking Dust
- ▶ Portable Air Conditioner Venting Hose

PROPERTIES:

- ► Good Resistance To Alkalis , Acids, Chemicals, UV & Ozone.
- ► Self-Supporting
- ► Simple Increase Or Reduction Of Size
- ► Maintains Shape
- ► Flame Retardant Acc To UL94-HB



STANDARD COLOUR:

► Grey

MARKING ON THE HOSE:

Na























ITEM		OD	WALL										
	ID		THICKNES S	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUM PRESSURE	EX-STOCK	мод
11RBPVC55	55.00	61.00	-	-	-	-	-	-	-	5	-	YES	5
11RBPVC65	65.00	71.00	-	-	-	-	-	-	-	5	-	YES	5
11RBPVC75	75.00	82.00	-	-	-	-	-	-	-	5	-	YES	5
11RBPVC90	90.00	95.00	-	-	-	-	-	-	-	5	-	NO	200
11RBPVC100	100.00	107.00	-	-	-	-	-	-	-	5	-	YES	5
11RBPVC125	125.00	133.00	-	-	-	-	-	-	-	5	-	NO	200
11RBPVC150	150.00	158.00	-	-	-	-	-	-	-	5	-	NO	200
11RBPVC200	200.00	208.00	-	-	-	-	-	-	-	5	-	NO	200

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

HDFC Bank A/c No: 5020 0006647 423 RTGS/NEFT IFSC:HDFC0000558