


TUBE:

- Thermoplastic Elastomer

REINFORCEMENT:

- Double Steel Wire Braids

COVER:

- Red / Orange Color, Polyurethane

TEMP RANGE:

- -40°C to +100°C
- Temp. Not to Exceed +70°C For Air & Water Based Fluids.

APPLICATIONS:

- Very High Pressure Hydraulic Lines 520 to 700 Bar.
- Compact, High Pressure, Light Weight & Low Change in Length.
- For use with Petroleum, Synthetic or Water Based Fluids in Hydraulic Systems.
- Suitable for Agricultural Machinery, Earthmoving, Articulating & Telescopic Booms and Material Handling Equipments.
- Mainly used for Rescue, Safety Equipments, Bolt Tensioning Tools & Jacking & Re-Railing Equipments.

PROPERTIES:

- Suitable for Hydraulic Application with Increased Resistance To Abrasion.

STANDARD COLOUR:

- Red

MARKING ON THE HOSE:

- JACK HOSE ID...MAX WP...PSI(...BAR)



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
501TPJACK04	6.40	14.10	3.85	700 10150	1750 25375	100	0.33	-	-	YES	5
501TPJACK06	9.50	17.50	4.00	700 10150	1750 25375	150	0.48	-	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.