


TUBE:

- ▶ Oil Resistant Synthetic Rubber

REINFORCEMENT:

- ▶ Four Or Six High Tensile Steel Spirals

COVER:

- ▶ Environment & Oil Resistant
- ▶ Synthetic Rubber

TEMP RANGE:

- ▶ -40°C to +100°C
- ▶ Intermittent Services 125°C

APPLICATIONS:

- ▶ Very High Pressure Power Lines

FEATURES:

- ▶ Weather, Abrasion & Oil Resistant

STANDARD COLOUR:

- ▶ Black

MARKING ON THE HOSE:

- ▶ HoseX 6S - EXCEEDS SAE J517 100 R13
1.1/2"-38.1 MM-WP 35Mpa/350 Bar/
5075 PSI-MSHA

APPLICABLE STANDARDS:

- ▶ SAE J 517 - 100 R13
- ▶ EN 856
- ▶ ISO 3862



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
501R1324	38.10	56.80	9.35	350 5075	1400 20300	530	4.44	40	-	YES	5
501R1332	50.80	70.40	9.80	350 5075	1400 20300	630	7.10	40	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).
 In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.