


TUBE:

Ester-Polyurethane with Smooth Interior Wall

REINFORCEMENT:

Spiral Hard PVC

COVER:

Corrugated with Hard PVC Spiral

TEMP RANGE:

 -20 °C Approx. to +70 °C Approx.
 Short Time to +80 °C Approx.

APPLICATIONS:

 For Abrasive Solids such as Dust, Powder, Fibers, Chip and Granulates.
 For Gaseous and Liquid Media
 For De-Dusting and Suction Plants, Industrial Vacuum Cleaner.
 Suction of Paper and Textile Fibers as Resistant Protection Hose.

PROPERTIES:

 Light Model
 Abrasion Proof
 Optimized Flow Properties
 Smooth Interior Layer
 Good Flexibility and Durability
 Good Resistance Alkalies, Acids, Chemicals, UV and Ozone.
 Small Bending Radius
 Gas and Liquid Tight
 Flame-Retardant Acc to UL 94-HB

STANDARD COLOUR:

Transparent

MARKING ON THE HOSE:

NA



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
11PUS25	25.00	31.00	-	1.00 -	- -	31	0.14	20	0.25	NO	300
11PUS32	32.00	38.00	-	0.85 -	- -	38	0.17	20	0.20	NO	300
11PUS38	38.00	45.00	-	0.75 -	- -	50	0.22	20	0.20	NO	300
11PUS40	40.00	47.00	-	0.75 -	- -	60	0.23	20	0.20	NO	300
11PUS50	50.00	58.00	-	0.50 -	- -	70	0.31	20	0.20	NO	150
11PUS60	60.00	68.00	-	0.50 -	- -	80	0.47	20	0.16	NO	150
11PUS63	63.00	71.00	-	0.45 -	- -	80	0.50	20	0.16	NO	150
11PUS76	76.00	85.00	-	0.40 -	- -	100	0.60	20	0.16	NO	150
11PUS100	100.00	110.00	-	0.28 -	- -	150	0.82	20	0.14	NO	90
11PUS125	125.00	136.00	-	0.25 -	- -	170	1.20	20	0.11	NO	60
11PUS150	150.00	162.00	-	0.18 -	- -	200	1.65	20	0.09	NO	60

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.

LALIT MACHINERY STORE

64 & 65, Ajmeri Gate, Delhi-110006

Contact : +91- 9555995522 | Email : Lms@hosexperts.com | Web : www.hosexperts.com

BANK DETAILS

HDFC Bank A/c No: 5020 0006647 423

RTGS/NEFT IFSC:HDFC0000558