


TUBE:

Specially Compounded Synthetic Rubber, Black

REINFORCEMENT:

High Strength Synthetic Plies With Helix Wire

COVER:

Black Synthetic Rubber Cover

TEMP RANGE:

-40°C to +70°C Approx

APPLICATIONS:

 For Suction & Discharge of Water & Non Corrosive
 Inert Fluid, Waste Water & Sewerage etc

FEATURES:

 Seamless
 Uniform Thickness
 Very Strong

STANDARD COLOUR:

 Inner Tube - Black
 Outer Cover - Black

MARKING ON THE HOSE:

 Indo-Makssson Hydro Water S&D Hose
 I.D. W.P India

APPLICABLE STANDARDS:

IS : 3549

													
	ID	OD	THICKNES S	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
ITEM	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1WTRSUC10KG38	38.00	51.00	6.50	10	150	30	435	230		40		NO	40
1WTRSUC10KG50	50.00	64.00	7.00	10	150	30	435	310		40		YES	5
1WTRSUC10KG63	63.00	78.00	7.50	10	150	30	435	380		40		YES	5
1WTRSUC10KG75	75.00	91.00	8.00	10	150	30	435	460		40		YES	5
1WTRSUC10KG100	100.00	119.00	9.50	10	150	30	435	610		40		YES	5
1WTRSUC10KG125	125.00	146.00	10.50	10	150	30	435	760		40		NO	40
1WTRSUC10KG150	150.00	173.00	11.50	10	150	30	435	920		40		NO	40

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.