


**TUBE:**

Specially Compounded Oil Resistant Synthetic Rubber, Black

**REINFORCEMENT:**

High Strength Synthetic Plies With Helix Wire

**COVER:**

Black Synthetic Rubber Cover Resistant to Oil

**TEMP RANGE:**

-26°C to +85°C Approx

**APPLICATIONS:**

For Suction & Discharge of Oil & Petroleum Grades With Aromatic Contents upto 50% from Tank Truck & Other Similar Industrial Solutions

**FEATURES:**

Seamless  
Uniform Thickness  
Flexible  
Very Strong

**STANDARD COLOUR:**












Inner Tube - Black  
Outer Cover - Black

**MARKING ON THE HOSE:**

Indo-Makssson Floil Suction & Discharge Hose  
I.D. W.P India

**APPLICABLE STANDARDS:**

Exceeds IS 10733 : Type 1B & 2B

													
ITEM	ID	OD	THICKNES	WORKING	BURSTING	BENDING	WEIGHT	STANDARD	VACCU	EX-STOCK	MOQ		
Code	mm	mm	S	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
1OIL10KG38	38.00	51.00	6.50	10	150	30	435	230		40		NO	40
1OIL10KG50	50.00	64.00	7.00	10	150	30	435	310		40		YES	5
1OIL10KG63	63.00	78.00	7.50	10	150	30	435	380		40		YES	5
1OIL10KG75	75.00	91.00	8.00	10	150	30	435	460		40		YES	5
1OIL10KG100	100.00	119.00	9.50	10	150	30	435	610		40		YES	5
1OIL10KG125	125.00	146.00	10.50	10	150	30	435	760		40		NO	40
1OIL10KG150	150.00	173.00	11.50	10	150	30	435	920		40		NO	40

Specification Subject to change due to Improvement in Quality ( E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.