


TUBE:

Specially Compounded Abrasion Resistant
Natural Rubber, High Resilience

REINFORCEMENT:

High Tensile Plies Synthetic With Copper Wire

COVER:

Black Abrasion Resistant Natural Rubber Cover
Fabric Impression

TEMP RANGE:

-20°C To +80°C

APPLICATIONS:

Abrasion Resistant Sand, Corundum, Shot & Grit
Blast Delivery Hose normally used for surface
treatment.
For Cleaning & Blasting Metal, Stone & Concrete
Surfaces.

PROPERTIES:

Seamless
Uniform Thickness
Smooth Bore
Mandrel Built

FEATURES:

Highly Abrasion Resistant Rubber Tube
Anti Static Copper Wire Embedded in the Hose

APPLICABLE STANDARDS:

IS: 5894

STANDARD COLOUR:

Inner Tube : Black
Outer Cover: Black

MARKING ON THE HOSE:


ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
501SBL30025	25.00	40.00	7.50	20 300	60 900	-	0.96	60	-	YES	5
501SBL30032	31.50	49.80	9.15	20 300	60 900	-	1.53	60	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.