


TUBE:

Black, Smooth, Natural and Synthetic Rubber

REINFORCEMENT:

High Tensile Textile Plies

COVER:

Black, Smooth, Weather & Abrasion Resistant Rubber.

TEMP RANGE:

-30°C Approx to +70°C Approx

APPLICATIONS:

 For Water Cleaning Equipment
 For High Pressure Washing

PROPERTIES:

 Seamless
 Uniform Thickness
 Smooth Bore
 Mandrel Built

FEATURES:

 Good Abrasion Resistance
 Heavy Wall Thickness

STANDARD COLOUR:

Grey with Black Strip

MARKING ON THE HOSE:

 Car Washing Hose Exceeds IS 444: Type 3B
 WP 50 Bar

APPLICABLE STANDARDS:

IS: 444 TYPE IIIB



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
3CW10	10.00	20.00	5.00	50 715	200 2860	-	0.36	100	-	YES	5
3CW12	13.00	24.00	5.50	50 715	200 2860	-	0.48	100	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).
 In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.