


TUBE:

Black, Smooth, Natural and Synthetic Rubber

REINFORCEMENT:

High Tensile Textile Plies

COVER:

Black, Smooth, Weather & Abrasion Resistant Rubber.

Smooth finish

TEMP RANGE:

-30°C Approx to +70°C Approx

APPLICATIONS:

Industrial & Construction Services with Medium Pressure Requirement.

Gardening & General Water Discharge Services

Suitable for Non Corrosive Fluids

Suitable for Air Discharge

PROPERTIES:

Seamless

Uniform Thickness

Smooth Bore

Mandrel Built

STANDARD COLOUR:

Black with Blue Strip

MARKING ON THE HOSE:

Heavy Duty Air/Water Hose Exceeds

IS 444:Type III/IS 446:1980 Type I

APPLICABLE STANDARDS:

IS 444:Type III/IS 446:1980 Type I



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
3WTR12.5	12.00	20.00	4.00	12 175	36 525	-	0.30	100	-	YES	5
3WTR19	20.00	31.00	5.50	12 175	36 525	-	0.67	100	-	YES	5
3WTR25	25.00	36.00	5.50	12 175	36 525	-	0.70	100	-	YES	5
3WTR32	32.00	44.00	6.00	12 175	36 525	-	0.98	61	-	YES	5
3WTR38	38.00	50.00	6.00	12 175	36 525	-	1.14	61	-	YES	5
3WTR50	50.00	63.00	6.50	12 175	36 525	-	1.46	61	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.