


TUBE:

Black, Smooth, Natural and Synthetic Rubber
Resistant to Abrasion.

REINFORCEMENT:

High Tensile Textile Plies with Anti Static Copper Wire.

COVER:

Black, Smooth, Weather & Abrasion Resistant Rubber.
Fabric Impression

TEMP RANGE:

-40°C Approx to +70°C Approx

APPLICATIONS:

Abrasion Resistant Sand, Corundum, Shot & Grit
Blast Delivery Hose normally used for surface treatment.
For Cleaning & Blasting Metal, Stone & Concrete Surfaces.

PROPERTIES:

Seamless
Uniform Thickness
Smooth Bore
Mandrel Built

FEATURES:

Highly Abrasion Resistant Rubber Tube
Anti Static Copper Wire Embedded in the Hose

STANDARD COLOUR:

Black with Brown Strip

MARKING ON THE HOSE:

Sand Blast Hose Exceeds IS 5894:1980
Type II Wp 10 Bar Mfg Sel HL/YP

APPLICABLE STANDARDS:

IS : 5894/90 TYPE I



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE		BURSTING PRESSURE		BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
3SBL20	19.00	33.00	7.00	10	145	30	435	-	0.67	61	-	NO	61
3SBL25	25.00	39.00	7.00	10	145	30	435	-	0.84	61	-	NO	61
3SBL32	32.00	48.00	8.00	10	145	30	435	-	1.36	61	-	NO	61
3SBL38	38.00	56.00	9.00	10	145	30	435	-	1.52	61	-	NO	61

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.