


TUBE:

Black EPDM Rubber Resistant to Chemicals

REINFORCEMENT:

High Tensile Textile Plies

COVER:

Black, Smooth, Weather, Abrasion & Ozone Resistant EPDM Rubber.

Fabric Impression

TEMP RANGE:

Temp & Concentration of the Transported Medium: Refer to Chemical Resistance Chart.

APPLICATIONS:

 For Discharge of Wide Range of Chemicals (Refer to Chemical Resistance Chart)
 Delivery Hose for Organic & Non - Organic Acids, Salts & Bases, Ketons & Paint with Water Basis.
 Also Suitable for Dye-Stuff for Cloth.

PROPERTIES:

 Seamless
 Uniform Thickness
 Smooth Bore
 Mandrel Built

STANDARD COLOUR:

Black with White & Blue Strip

MARKING ON THE HOSE:

Chemical Hose Exceeds IS 7654/1975 Type I HY/YP

APPLICABLE STANDARDS:

IS : 7654/1975 Type I



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
3CHL25	25.00	37.00	6.00	12 175	48 700	-	0.67	61	-	YES	5
3CHL32	32.00	44.00	6.00	12 175	48 700	-	0.85	61	-	YES	5
3CHL38	38.00	50.00	6.00	12 175	48 700	-	0.98	61	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).
 In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.