


TUBE:

Synthetic NBR Rubber, Resistant to Oil Mist Mixed Air & Inert Fluids.

REINFORCEMENT:

High Tensile Textile Plies

COVER:

Black, Smooth, Weather & Abrasion Resistant Synthetic Rubber.

Smooth finish upto 25mm, Fabric impression 32mm onwards.

TEMP RANGE:

-30°C Approx to +80°C Approx

APPLICATIONS:

Heavy Duty Service for Air specially in Mines, Quarries & Constructions.

Suitable for Air with Oil Mist, for Compressors, Bore & Pneumatic Machines.

PROPERTIES:

Seamless
Uniform Thickness
Smooth Bore
Mandrel Built

STANDARD COLOUR:

Black with Green Strip

MARKING ON THE HOSE:

Rock Drill Hose Exceeds IS 446:1980 Type III

APPLICABLE STANDARDS:

IS : 446/1980 Type III



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
3RD12	13.00	22.50	4.75	20	300	60	0.40	100	-	YES	5
3RD20	20.00	31.00	5.50	20	300	60	0.67	100	-	YES	5
3RD25	25.00	36.00	5.50	20	300	60	0.69	100	-	YES	5
3RD32	32.00	44.00	6.00	16	230	48	1.02	61	-	YES	5
3RD38	38.00	52.00	7.00	16	230	48	1.36	61	-	YES	5
3RD50	50.00	64.00	7.00	16	230	48	1.66	61	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).

In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.