


**TUBE:**

Black, Smooth, Natural and Synthetic Rubber

**REINFORCEMENT:**

High Tensile Textile Plies

**COVER:**

Black, Smooth, Weather &amp; Abrasion Resistant Rubber.

**TEMP RANGE:**

-30°C Approx to +70°C Approx

**APPLICATIONS:**

 For Water Cleaning Equipment  
 For High Pressure Washing  
 High Pressure Spray of Agricultural Pesticides

**PROPERTIES:**

 Seamless  
 Uniform Thickness  
 Smooth Bore  
 Mandrel Built

**FEATURES:**

 Good Abrasion Resistance  
 Heavy Wall Thickness

**STANDARD COLOUR:**

Black with Grey Strip

**MARKING ON THE HOSE:**

Super Spray Hose Exceeds IS 1667:1968 Type 4B

**APPLICABLE STANDARDS:**

IS 1667:1968 Type 4B



ITEM	ID	OD	WALL THICKNESS	WORKING PRESSURE	BURSTING PRESSURE	BENDING RADIUS	WEIGHT	STANDARD LENGTH	VACCUUM PRESSURE	EX-STOCK	MOQ
Code	mm	mm	mm	Bar PSI	Bar PSI	mm	Kg/mtr	mtr	Bar	---	mtr
3SS10	10.00	20.00	5.00	50 725	200 2900	-	0.36	100	-	YES	5
3SS12	13.00	24.00	5.50	50 725	200 2900	-	0.50	100	-	YES	5

Specification Subject to change due to Improvement in Quality (E&O.E).  
 In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.