


**TUBE:**

EPDM Rubber Resistant to Saturated Steam

**REINFORCEMENT:**

High Tensile Textile Plies

**COVER:**

Black, Smooth, Weather, Abrasion, Heat, Steam &amp; Ozone Resistant Pin Pricked Special Synthetic Rubber.

Fabric Impression

**TEMP RANGE:**

-40°C Approx to +165°C Approx

**APPLICATIONS:**

 For General Saturated Steam Services  
 For Cleaning & Sterlization with Steam

**PROPERTIES:**

 Seamless  
 Uniform Thickness  
 Smooth Bore  
 Mandrel Built

**STANDARD COLOUR:**

Black with White Strip

**MARKING ON THE HOSE:**

 Steam Hose Exceeds IS 5122:1975 Type II  
 WP 7 Bar

**APPLICABLE STANDARDS:**

IS : 5122/1975 Type II



ITEM	ID	OD	WALL		WORKING		BURSTING		BENDING	STANDARD	VACCU	EX-STOCK	MOQ
			THICKNES	S	PRESSURE	PRESSURE	RADIUS	WEIGHT					
Code	mm	mm	mm	Bar	PSI	Bar	PSI	mm	Kg/mtr	mtr	Bar	---	mtr
3STM12.7	13.00	25.00	6.00	7	100	70	1000	-	0.39	61	-	YES	5
3STM19	19.00	33.00	7.00	7	100	70	1000	-	0.62	61	-	YES	5
3STM25	25.00	38.00	6.50	7	100	70	1000	-	0.68	61	-	YES	5
3STM32	32.00	44.00	6.00	7	100	70	1000	-	0.79	61	-	YES	5
3STM38	38.00	50.00	6.00	7	100	70	1000	-	0.92	61	-	YES	5

Specification Subject to change due to Improvement in Quality ( E&O.E).  
 In the interest of Continual Development, the Company reserves the right to make modifications to these details without prior notice.